



NB7W-TW00B

Touch screen HMI, 7 inch WVGA (800 x 480 pixel), TFT color

Specifications

Screen diagonal	7 inch
Number of pixels, horizontal	800
Number of pixels, vertical	480
Type of display	TFT
Frame colour	Black
Number of Ethernet ports	0
Number of RS-232 ports	2
Number of RS-422 ports	1
Number of RS-485 ports	1
Number of USB ports	2
Number of colours of the display	65536
Number of grey-scales/blue-scales of display	64
Degree of protection (IP), front side	IP65
Width of the front	202.0 mm
Height of the front	148 mm
Width of panel cutout	191 mm
Height of panel cutout	137 mm
Built-in depth	46 mm
Weight	1000 g

Accessories



CP1W-CN221

USB Programming cable, A-type male to B-type male, 1.8 m



NB7W-KBA04

Protective sheets for NB7W (5 sheets)



XW2Z-200T

Cable, RS-232C, for connecting NT HMI 9-pin port to PLC 9-pin port, 2 m



XW2Z-500T

Cable, RS-232C, for connecting NT HMI 9-pin port to PLC 9-pin port, 5 m

Downloads

CAD Library



EVE CR-series button cells
Battery Safety Datasheet

EN PDF 63 KB



Faceplates for HMI 2.0
(14 languages)
Software

EN ZIP 72.2 MB



NB Series HMI
Datasheet

EN PDF 5.26 MB



NB-Designer Setup
v1.5.2.0

Software

EN ZIP 374 MB



NB-Designer Setup
v1.5.3.1

Software

EN ZIP 374 MB



NB-Series
Setup Manual

EN PDF 10 MB



NB-Series
Getting Started Guide

EN PDF 12.2 MB



NB-Series Host
Connection
Setup Manual

EN PDF 14.8 MB



NB7W-TW1_B HMIs
Users Manual

EN PDF 40.7 MB

